AMGO Lift

FOUR POST PARKING LIFTS

Incorporating an exclusive concealed lock-control mechanism alongside a dual-lock system, the AMGO double parking series has been engineered to maximize garage efficiency while affording enhanced security—enabling up to four vehicles to be parked within one lift. The inclusion of a remote control ensures effortless operation, while integrated limit switches provide an additional safety measure. Furthermore, its compatibility with back-to-back installation offers even greater spatial efficiency, making it the ideal solution for multi-car parking, with a robust lifting capacity of up to 4,000 kg.



A440-DP (4000KG) **A440-DPX** (4000KG)

Invention Patent 2023232158140

SPECIFICATIONS



Model		A440-DP	A440-DP
Style		Double parking four post lift	Double parking four post lift
Lifting capacity		4000kg	4000kg
Lifting time		47S	57S
Overall Length (Inc. Ramps)	A	5285mm	6061mm
Overall Length (No Ramps)	B	4258mm	5032mm
Overall Width	C	4840mm	4840mm
Width Between Columns	D	4598mm	4598mm
Drive Through Width	E	4314mm	4314mm
Overall Height	F	2105mm	2455mm
Minimum Height	G	150mm	150mm
Lifting Height	H	1870mm	2232mm
Max. Lock Lifting Height to top of runway	H	1800mm	2162mm
Max. Underneath Height	I	1750mm	2112mm
Max. Lock Underneath runway	I	1680mm	2042mm
Width Between Runways	J	940mm	940mm
Overall Width of Single Parking Unit	K	1890mm	1890mm
Width Between Two Parking Units	L	350mm	350mm
Gross Weight		1262kg	1372kg
Motor		3.0HP	3.0HP





A440-DP
(4000KG)



Effortless remote control operation.

FEATURES

- 4000KG capacity, max single car weight: 2800kg;
- Double Parking design, 1 lift, 4 parking seats;
- AMGO's exclusive concealed lock control system with manual release;
- Dual-lock mechanism equipped as standard for enhanced security and comfort;
- Minimum height only 150mm, easy access for various vehicles;
- Integrated anti-slippy platforms;
- Standard remote control operation ensures conveninent use ;
- Support back to back installation to improve space efficiency;
- Double-S shaped columns for added strength;
- Foldable drive-on ramps come standard;
- A limit switch is fitted as standard to enhance safety;
- No need for additional air supply.

A440-DPX
(4000KG)



Patented concealed safety lock control with single-point manual release.



Support back to back installation to improve space efficiency.



Double safety locks provide additional safety.



Foldable drive-on ramp equipped as standard.



Optional extended aluminum drive-in ramps (1PC).
Kits No.: 40815



Optional plastic oil tray (1 set,4pcs)



Optional rubber wheel chock.
P/N: 40811.



Optional storage wave panel.
P/N:40821.



Optional J5H sliding jack (capacity: 2200kg), with hand pump. 2.5" extension adapters included.